SAFETY DATA SHEET

Issue Date 27-May-2015

Revision Date 03-Jul-2019

Version 4

1. IDENTIFICATION

Product identifier Product Name

Wolmanized[®] Outdoor[®] Wood (MCA-C)

Other means of identification Product Code Synonyms

23453 Copper Azole Treated Wood

Recommended use of the chemical and restrictions on useRecommended UseTreated Wood.

Details of the supplier of the safety data sheetSupplier AddressManufacturer AddressCustomers and Licensees of:Arch Treatment Technologies, Inc - ALonza Company3941 Bonsal RoadConley, GA 30288

Emergency telephone number Company Phone Number 24 Hour Emergency Phone Number : Emergency Telephone

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Skin corrosion/irritation	Category 3
Serious eye damage/eye irritation	Category 2B
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3

Label elements

Emergency Overview

Danger

Hazard statements May cause cancer Causes eye irritation



Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Disposal

Dispose of contents/ container to an approved landfill

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Causes mild skin irritation

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Synonyms

Copper Azole Treated Wood.

Chemical Name	CAS No.	Weight-%	Trade Secret
Wood and Wood Dust	NOT ASSIGNED	95 - 100	
(Copper (II) carbonatecopper(II) hydroxide (1:1))	12069-69-1	0.1 - 1	
Propiconazole	60207-90-1	<0.1	
Tebuconazole	107534-96-3	<0.1	

4. FIRST AID MEASURES

Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not rub affected area.	
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Inhalation	Remove to fresh air. Call a physician immediately. If not breathing, give artificial respiration.	
Ingestion	If swallowed, call a poison control center or physician immediately. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	See Section 11: TOXICOLOGICAL INFORMATION.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide (CO2). Water spray or fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

No information available.

Hazardous combustion productsCarbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas.

For emergency responders	Use personal protection recommended in Section 8.		
Environmental precautions			
Environmental precautions	See Section 12: ECOLOGICAL INFORMATION.		
Methods and material for containr	nent and cleaning up		
Methods for containment	Cover powder spill with plastic sheet or tarp to minimize spreading.		
Methods for cleaning up	Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically, placing in appropriate containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly. Take precautionary measures against static discharges.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Do not burn treated wood. Do not use pressure treated chips or sawdust as mulch. Use with local exhaust ventilation. Avoid generation of dust. May form combustible dust concentrations in air. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Do not breathe dust/wist/vapors/spray.		

Conditions for safe storage, including any incompatibilities

Storage Conditions	Avoid generation of dust.
Incompatible materials	None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Wood and Wood Dust	1.0 mg/m ³ Inhalable,	15 mg/m ³ Total Dust	-
NOT ASSIGNED	0.5 mg/m ³ Inhalable Western Red	5.0 mg/m ³ Respirable Fraction	
	Cedar		
(Copper (II) carbonatecopper(II)	TWA: 1 mg/m ³ Cu dust and mist	-	IDLH: 100 mg/m ³ Cu dust and mist
hydroxide (1:1))			TWA: 1 mg/m ³ Cu dust and mist
12069-69-1			-

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers. Eyewash stations. Ventilation: Saw, cut or machine wood outdoors or in well ventilated areas. Due to the explosive potential of dust when suspended in air, precautions should be taken when sawing, sanding, or machining wood or wood products to prevent sparks or other ignition sources. If required, use wet methods and/or explosion suppression systems to reduce generation of dust. Local exhaust ventilation is

recommended when sawing, sanding, or machining this product. General dilution ventilation is recommended in processing and storage areas.

Individual protection measures, such as personal protective equipment

Eye/face protection	Use safety glasses with side shields or chemical goggles when sawing or cutting treated or untreated wood.
Skin and body protection	Wear leather gloves. Wear long sleeve shirt, pants, and steel-toed shoes when handling treated or untreated wood.
Respiratory protection	None normally required. When sawing or cutting treated or untreated wood, wear a NIOSH approved N95 or better dust mask.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off all contaminated clothing and wash it before reuse. Avoid contact with skin, eyes or clothing. Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Solid No information available light green	Odor Odor threshold	No information available No information available
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties	Values No information available No information available <th><u>Remarks • Method</u></th> <th></th>	<u>Remarks • Method</u>	
Oxidizing properties <u>Other Information</u>	No information available		
Softening point Molecular weight VOC Content (%)	No information available No information available No information available		

Density Bulk density

No information available No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	WOOD and WOOD DUST :. May cause cancer. May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Eye contact	WOOD and WOOD DUST :. Irritating to eyes.	
Skin contact	WOOD and WOOD DUST :. May cause irritation. May cause allergic skin reaction.	
Ingestion	WOOD and WOOD DUST :. Harmful if swallowed.	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
(Copper (II) carbonatecopper(II) hydroxide (1:1)) 12069-69-1	= 1350 mg/kg (RT)	>2000 mg/kg (RT)	1.03 - 5.2 mg/L (RT) 4h
Propiconazole 60207-90-1	= 1517 mg/kg (RT)	> 4000 mg/kg (RT)	>5.8 mg/L (RT) 4h
Tebuconazole 107534-96-3	>1700 mg/kg (RT)	> 2000 mg/kg (RT)	> 5.0 mg/L (RT) 4h

Note: RT = Rat RBT = Rabbit MSE = Mouse GP = Guinea Pig V = Vapour

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Jan 2011 Jan				
Chemical Name	ACGIH	IARC	NTP	OSHA
Wood and Wood Dust	Х	Group 1	Х	Х
NOT ASSIGNED				

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Numerical measures of toxicity - Product Information

ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) **ATEmix (inhalation-vapor)**

Numerical measures of toxicity

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
(Copper (II) carbonatecopper(II) hydroxide (1:1)) 12069-69-1	0.043 mg/L EC50 96h (Desmodesmus suspicatus)	0.087 mg/L LC50 96h (Oncorhynchus mykiss)	0.042 mg/L EC50 48h (Daphnia magna)
Propiconazole	0.76 mg/L EC50 (Desmodesmus	4.3 mg/L LC50 96h (Oncorhyncus mykiss)	10.2 mg/L EC50 48h (Daphnia
60207-90-1	subspicatus)		magna)
Tebuconazole	3.8 mg/L EC50 72h	4.4 mg/L LC50 48h (Oncorhyncus mykiss)	2.79 mg/L EC50 48h (Daphnia
107534-96-3	(Pseudokirchneriella subcapitata)		magna)

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is not a hazardous waste according to state and federal regulations (40 CFR 261). Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

No information available.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
(Copper (II) carbonatecopper(II) hydroxide (1:1))	Toxic
12069-69-1	

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
(Copper (II)	-	Х	-	-

carbonatecopper(II)		
hydroxide (1:1))		
12069-69-1		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Propiconazole	-	Х	-
60207-90-1			

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Wood and Wood Dust - NOT ASSIGNED	Carcinogen
Formaldehyde - 50-00-0	Carcinogen
Naphthalene - 91-20-3	Carcinogen

Warning: This wood contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Sodium sulfate 7757-82-6	-	X	Х
Formaldehyde 50-00-0	X	X	Х
Naphthalene 91-20-3	X	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection X

27-May-2015

03-Jul-2019

Issue Date Revision Date Revision Note No information available Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet